

MPM 5/225 I-EB/H

- + PETROL ENGINE DRIVEN WELDER/GENERATOR / DELIVERS 225 A OF DC WELD OUTPUT / THREE-PHASE AND SINGLE-PHASE AUXILIARY POWER AVAILABLE

Gen Set Features

Processes: STICK

- + Low oil level cut out device
- + 1 x 400 V - 50 Hz three-phase outlet
- + 1 x 230 V - 50 Hz Single-phase outlet protected by circuit breaker
- + Earth Leakage Circuit Breaker (ELCB)
- + Voltmeter

Gen Set Options

(available as factory options)

- + Versions with different voltages
- + 60 Hz version

Accessories on Request

- + Trolley: two-wheels and handles
- + Welding cables \varnothing 35 mm² (5+3 m) with accessories

Noise Level

- + LWA 98 (73 dB at 7m)

DC Welding

- + Duty Cycle @ 35% 225 A - 29 V
- + Duty Cycle @ 60% 170 A - 27 V
- + Output Range 40 A ÷ 225 A
- + Open Circuit Voltage 90 V
- + Max welding rod 5 mm

AC Generator - 50 Hz

- + Type Gen Set asynchronous self-excited and self-protected
- + Three-phase Power 5 kVA - 400 V
- + Single-phase Power 4 kVA - 230 V
- + Power Factor 0,8

Petrol Engine 3000 rpm

- + Type **Honda GX 390 OHV** - 1cyl. - 13HP (9,6kWm) - 390 cm³
- + Fuel petrol
- + Cooling system air
- + Starting system manual recoil
- + Fuel tank capacity 6,5 l
- + Fuel consumption @ 75% 2,9 l/h

Other Features

- + Insulation Class F
- + Mechanical Protection IP 23
- + Dimensions (L x W x H) 720 x 480 x 515 mm
- + Net Weight 96 kg

+ MPM 5/225 I-EB/H

